



## TECHNICAL SPECIFICATIONS

Dust extraction	Included	Excluded
<b>Length of drum</b>	4 m	4 m
<b>Capacity</b>	5 mill. splints / hour	5 mill. splints / hour
<b>Attendants</b>	-	-
<b>Power required</b>		
- Main drive motor	1.54 kW	1.5 kW
- Dust extraction	3.0 kW	-
<b>Net weight</b>	3,300 kg	2,900 kg
<b>Gross weight</b>	4,800 kg	3,900 kg
<b>Shipping volume</b>	38.5 m <sup>3</sup>	26.7 m <sup>3</sup>

# Arenco–FZD5 Polishing Drum

## DESCRIPTION OF FEATURES

The polishing drum FZD is a rotating, hexagonal drum mounted on a heavy stand. The drum declines to the discharge end, and the internal surfaces of the drum are smooth. During the tumbling motion resulting from the rotation of the drum the splints are polished by working against each other.

The inlet is designed for air transported splints, cyclone not provided, but can also be delivered to fit conveyor feed. The discharge end is designed to allow direct feed of the polished splints into the cleaning machine.

The drum is provided with a discharge funnel which is shaped to permit the connection of a dust extraction nozzle. As standard, the drum is supplied with a dust collecting arrangement comprising bag filter with fan.

*Design and specifications may be modified without notice.*

**Spare part orders and service, new machine inquiries, mechanical repairs and preventive maintenance,** contact us at [info@arenco.com](mailto:info@arenco.com) or call +46 480 945 00

